

# VECTOR



**Artemide**<sup>®</sup>  
ARCHITECTURAL




For further information on Vector  
visit [artemide.com](http://artemide.com)

# Vector

With a simple and elegant form that hides a great mechanical and optoelectronic intelligence, Vector is able to respond with richness and variety of performance suitable for retail and beyond.









# Vector is smart design

Carlotta de Bevilacqua  
2017

# Vector typologies

## Track 230V



Vector 40



S 13° F 20° WF 28°  
10W 10W 10W  
540 lm 584 lm 528 lm



Vector 55



S 16° F 22° WF 32°  
25W 25W 25W  
1492 lm 1465 lm 1596 lm



Vector 55 Zoom



F 22°- WF 32°  
23W  
660 - 1137 lm



Vector 95



S 16° F 24° WF 60°  
35W 35W 35W  
3118 lm 3122 lm 3119 lm

## Magnetic 48Vdc



Vector 40



S 13° F 20° WF 28°  
10W 10W 10W  
540 lm 584 lm 528 lm



Vector 55



S 16° F 22° WF 32°  
26W 26W 26W  
1492 lm 1465 lm 1596 lm



Vector 55 Zoom



F 22°- WF 32°  
23W  
660 - 1137 lm

## Semirecessed



Vector 40



S 13° F 20° WF 28°  
8W 8W 8W  
540 lm 584 lm 528 lm



Vector 55



S 16° F 22° WF 32°  
21W 21W 21W  
1492 lm 1465 lm 1596 lm

## Recessed



Vector 40



S 13° F 20° WF 28°  
8W 8W 8W  
540 lm 584 lm 528 lm



Vector 55



S 16° F 22° WF 32°  
17,5W 17,5W 17,5W  
1248 lm 1225 lm 1356 lm

## Pendant magnetic 48Vdc



Vector 40 Pendant



S 13° F 20° WF 28°  
10W 10W 10W  
540 lm 584 lm 528 lm



Vector 55 Pendant



S 16° F 22° WF 32°  
26W 26W 26W  
1492 lm 1465 lm 1596 lm

# Vector colors



Fast delivery



Delivery  
time on demand





# Vector color temperatures




Fast delivery




Delivery time on demand



Magnetic





Track



Vector  
dimensions

# Vector is fully addressable



Each spot can be managed separately  
by Artemide App or DALI control  
up to 64 IP Address





Artemide  
App  
Compatible



# Vector is balanced

The junction arm is integrated with the spotlight body.  
The center of balance is perfectly aligned with the track.  
The pivoting of the body and the arm orientation are lockable.





**Vector  
is zoom**



ANTI-DAZZLE LOUVRE



# Vector multiple accessories

ACCESSORIES HOLDER



ADJUSTABLE DOWSERS



SOFT FILTER



# Vector track 230V



Vector 55 Zoom Track 230V



Vector track 230V

White  
01  
Fast delivery

Black  
04

Brushed Silver  
15  
Delivery time on demand

Brushed Copper  
18

Brushed Bronze  
20

S

F

WF


IP20

MacAdam 3SDCM

Life L70 (6K) 50000h


Vector 40 track 230V

Track slim adapter					Undimmable		Dimmable DALI	
W	CRI	Beam	Flux	CCT	Code		Code	
10 W	90	S 13°	540 lm	2700K	<b>AN011.</b> 01/04		<b>AN016.</b> 01/04	
					15/18/20		15/18/20	
				3000K	<b>AN001.</b> 01/04		<b>AN006.</b> 01/04	
					15/18/20		15/18/20	
		F 20°	584 lm	2700K	<b>AN051.</b> 01/04		<b>AN056.</b> 01/04	
					15/18/20		15/18/20	
				3000K	<b>AN012.</b> 01/04		<b>AN017.</b> 01/04	
					15/18/20		15/18/20	
		WF 28°	528 lm	2700K	<b>AN002.</b> 01/04		<b>AN007.</b> 01/04	
					15/18/20		15/18/20	
				3000K	<b>AN052.</b> 01/04		<b>AN057.</b> 01/04	
					15/18/20		15/18/20	
				4000K	<b>AN013.</b> 01/04		<b>AN018.</b> 01/04	
					15/18/20		15/18/20	
				3000K	<b>AN003.</b> 01/04		<b>AN008.</b> 01/04	
				4000K	<b>AN053.</b> 01/04		<b>AN058.</b> 01/04	
					15/18/20		15/18/20	



Vector 55 track 230V

Track slim adapter					Undimmable		Dimmable DALI	
W	CRI	Beam	Flux	CCT	Code		Code	
25 W	90	S 16°	1492 lm	2700K	<b>AN111.</b> 01/04		<b>AN116.</b> 01/04	
					15/18/20		15/18/20	
				3000K	<b>AN101.</b> 01/04		<b>AN106.</b> 01/04	
					15/18/20		15/18/20	
		F 22°	1465 lm	2700K	<b>AN151.</b> 01/04		<b>AN156.</b> 01/04	
					15/18/20		15/18/20	
				3000K	<b>AN112.</b> 01/04		<b>AN117.</b> 01/04	
					15/18/20		15/18/20	
		WF 32°	1596 lm	2700K	<b>AN102.</b> 01/04		<b>AN107.</b> 01/04	
					15/18/20		15/18/20	
				3000K	<b>AN152.</b> 01/04		<b>AN157.</b> 01/04	
					15/18/20		15/18/20	
				4000K	<b>AN113.</b> 01/04		<b>AN118.</b> 01/04	
					15/18/20		15/18/20	
				3000K	<b>AN103.</b> 01/04		<b>AN108.</b> 01/04	
				4000K	<b>AN153.</b> 01/04		<b>AN158.</b> 01/04	
					15/18/20		15/18/20	




Vector track 230V

-90° 90° 360°


Vector 55 zoom track 230V






Track slim adapter					Dimmable DALI	
W	CRI	Beam	Flux	CCT	Code	
23 W	90	F 22°-WF 32°	660 - 1137 lm	2700K	<b>AN119.</b> 01/04	
					15/18/20	
				3000K	<b>AN109.</b> 01/04	
				4000K	<b>AN159.</b> 01/04	
					15/18/20	



Vector 95 track 230V

Track small adapter					Undimmable		Dimmable DALI		Dimmable DALI Eutrac	
W	CRI	Beam	Flux	CCT	Code		Code		Code	
35 W	90	S 16°	3118 lm	2700K	<b>AN211.</b> 01/04		<b>AN216.</b> 01/04		<b>AN316.</b> 01/04	
					15/18/20		15/18/20		15/18/20	
				3000K	<b>AN201.</b> 01/04		<b>AN206.</b> 01/04		<b>AN306.</b> 01/04	
					15/18/20		15/18/20		15/18/20	
		F 24°	3122 lm	2700K	<b>AN251.</b> 01/04		<b>AN256.</b> 01/04		<b>AN356.</b> 01/04	
					15/18/20		15/18/20		15/18/20	
				3000K	<b>AN212.</b> 01/04/		<b>AN217.</b> 01/04		<b>AN317.</b> 01/04	
					15/18/20		15/18/20		15/18/20	
		WF 60°	3119 lm	2700K	<b>AN202.</b> 01/04		<b>AN207.</b> 01/04		<b>AN307.</b> 01/04	
					15/18/20		15/18/20		15/18/20	
				3000K	<b>AN252.</b> 01/04		<b>AN257.</b> 01/04		<b>AN357.</b> 01/04	
					15/18/20		15/18/20		15/18/20	
				4000K	<b>AN213.</b> 01/04		<b>AN218.</b> 01/04		<b>AN318.</b> 01/04	
					15/18/20		15/18/20		15/18/20	
				3000K	<b>AN203.</b> 01/04		<b>AN208.</b> 01/04		<b>AN308.</b> 01/04	
				4000K	<b>AN253.</b> 01/04		<b>AN258.</b> 01/04		<b>AN358.</b> 01/04	
					15/18/20		15/18/20		15/18/20	



Accessoires		Vector 40		Vector 55		Vector 95	
		Color		Code		Code	
	Accessories holder	<b>AP90100</b>		<b>AP91100</b>		<b>AP92100</b>	
	Lens for elliptical emission	<b>AP90200</b>		<b>AP91200</b>		<b>M282007</b>	
	Soft filter	<b>AP90300</b>		<b>AP91300</b>		<b>M056807</b>	
	Anti-dazzle louvre	<b>AP90400</b>		<b>AP91400</b>		<b>M282100</b>	
	Adjustable dowisers ●			<b>AP91500</b>		<b>M059910</b>	

Track 230V

White

Black



01



















04

External three-circuit track

Track	
Length	
1000 mm	
2000 mm	
3000 mm	
4000 mm	

Code	
TK001.	01/04
TK002.	01/04
TK003.	01/04
TK004.	01/04



Accessories		Joint	
 End cap	Code TK005. 01/04	 Recessed joint	Code TK008. 01/04
 Power supply end cap Earth conductor on the left.	TK006. 01/04	 Linear joint	TK009. 01/04
 Power supply end cap Earth conductor on the right.	TK007. 01/04		
 Universal hook Maximum load 10 kg	TK200. 01/04	 90° joint Internal earth conductor.	TK010. 01/04
		 90° joint External earth conductor.	TK011. 01/04
 Kit suspension cables L. 1500 mm L. 3000 mm L. 5000 mm	TK20100 TK20200 TK20300	 3-way joint Earth conductor on right.	TK012. 01/04
		 3-way joint Earth conductor on left.	TK013. 01/04
 Stem kit L. 1000 mm	TK204. 01/04	 4-way joint	TK014. 01/04
 Plastic cup for steel cable Ø 1,5 mm	TK20501	 Flexible joint	TK015. 01/04
 T bracket for suspension	TK20600		
 Universal adapter 6 conductors 4 conductors	TK207. 01/04 TK208. 01/04		
 Accessory for ceiling installation	TK209. 01/04		

Track 230V

White

Black



01






04

Recessed three-circuit track

Track	
Length	
2000 mm	
3000 mm	
4000 mm	

Code	
TK102	01/04
TK103	01/04
TK104	01/04




Accessories		Joint	
 End cap	Code TK10501	 Recessed joint	Code TK10601
 Power supply end cap Earth conductor on the left.	TK108. 01/04		
 Power supply end cap Earth conductor on the right.	TK107. 01/04		
 Universal adapter 6 conductors 4 conductors	TK207. 01/04 TK208. 01/04		

The system is a 3 phase mixed system with two additional conductors intended to manage a general data signal (for example DALI, DMX, Ion, eib, etc.).

The system is EN 60570 certified and its installation must be accomplished by highly qualified person.

There are four possible installation systems: directly on ceiling or on wall, using the needlepoints on the track, on ceiling or on wall using a metal clip, hanging by the suspension or recessed without exceeding the maximum loads.

# Vector recessed



## Vector recessed

White  
01  
Fast delivery

Black  
04

Brushed Silver  
15  
Delivery time on demand

Brushed Copper  
18

Brushed Bronze  
20

S

F

WF


MacAdam 3SDCM  
Life L70 (6K) 50000h  
Trimless recessed structure not included,  
to be ordered separately.  
Driver 700/500mA SELV supplied separately.

-90° 90°  
360°

IP20  
ø 86 mm


## Vector 40 recessed



W	CRI	Beam	Flux	CCT	Code
8 W	90	S 13°	540 lm	2700K	<b>AP521.</b> 01/04 15/18/20
				3000K	<b>AP501.</b> 01/04 15/18/20
				4000K	<b>AP551.</b> 01/04 15/18/20
		F 20°	584 lm	2700K	<b>AP522.</b> 01/04 15/18/20
				3000K	<b>AP502.</b> 01/04 15/18/20
				4000K	<b>AP552.</b> 01/04 15/18/20
		WF 28°	528 lm	2700K	<b>AP523.</b> 01/04 15/18/20
				3000K	<b>AP503.</b> 01/04 15/18/20
				4000K	<b>AP553.</b> 01/04 15/18/20



## Vector 55 recessed

W	CRI	Beam	Flux	CCT	Code
17,5 W	90	S 16°	1248 lm	2700K	<b>AP531.</b> 01/04 15/18/20
				3000K	<b>AP511.</b> 01/04 15/18/20
				4000K	<b>AP561.</b> 01/04 15/18/20
		F 22°	1225 lm	2700K	<b>AP532.</b> 01/04 15/18/20
				3000K	<b>AP512.</b> 01/04 15/18/20
				4000K	<b>AP562.</b> 01/04 15/18/20
		WF 32°	1356 lm	2700K	<b>AP533.</b> 01/04 15/18/20
				3000K	<b>AP513.</b> 01/04 15/18/20
				4000K	<b>AP563.</b> 01/04 15/18/20



	Vector 40	Vector 55
	Code	Code
	Trimless recessed structure <b>AP50000</b>	<b>AP50000</b>
	Optional trim frame Ø 108 <b>AP590.</b> 01/04	<b>AP591.</b> 01/04

	Driver	Vac	L <sub>mm</sub>	W <sub>mm</sub>	H <sub>mm</sub>		Code
Vector 40	15-32W 700mA*	220-240	146,5	43,5	22	Undimmable	DV1030
Vector 55	15-32W 500mA	220-240	146,5	43,5	22	Undimmable	DV1030
Vector 40	11-25W 700mA	220-240	164	38	24,5	Dimmable DALI	DV1031
Vector 55	11-25 W 500mA	220-240	164	38	24,5	Dimmable DALI	DV1031

\* 1 Driver for Max 3 Spots



# Vector semirecessed



## Vector semirecessed

White 01 Fast delivery	Black 04	Brushed Silver 15 Delivery time on demand	Brushed Copper 18	Brushed Bronze 20	S F WF	MacAdam 3SDCM Life L70 (6K) 50000h Trimless recessed structure not included, to be ordered separately. Driver 700/600mA SELV supplied separately.	-90° 90° IP20 360° ø 50 mm
------------------------------	-------------	---	----------------------	----------------------	--------------	---	-------------------------------------


### Vector 40 semirecessed

W	CRI	Beam	Flux	CCT	Code
8 W	90	S 13°	540 lm	2700K	<b>AP621.</b> 01/04 15/18/20
				3000K	<b>AP601.</b> 01/04 15/18/20
				4000K	<b>AP651.</b> 01/04 15/18/20
			584 lm	2700K	<b>AP622.</b> 01/04 15/18/20
				3000K	<b>AP602.</b> 01/04 15/18/20
				4000K	<b>AP652.</b> 01/04 15/18/20
		WF 28°	528 lm	2700K	<b>AP623.</b> 01/04 15/18/20
				3000K	<b>AP603.</b> 01/04 15/18/20
				4000K	<b>AP653.</b> 01/04 15/18/20



### Vector 55 semirecessed

W	CRI	Beam	Flux	CCT	Code
21W	90	S 16°	1492 lm	2700K	<b>AP631.</b> 01/04 15/18/20
				3000K	<b>AP611.</b> 01/04 15/18/20
				4000K	<b>AP661.</b> 01/04 15/18/20
			1465 lm	2700K	<b>AP632.</b> 01/04 15/18/20
				3000K	<b>AP612.</b> 01/04 15/18/20
				4000K	<b>AP662.</b> 01/04 15/18/20
		WF 32°	1596 lm	2700K	<b>AP633.</b> 01/04 15/18/20
				3000K	<b>AP613.</b> 01/04 15/18/20
				4000K	<b>AP663.</b> 01/04 15/18/20



	Driver	Vac	L <sub>mm</sub>	W <sub>mm</sub>	H <sub>mm</sub>		Code
Vector 40	15-32W 700mA*	220-240	146,5	43,5	22	Undimmable	DV1030
Vector 55	15-32W 600mA	220-240	146,5	43,5	22	Undimmable	DV1030
Vector 40	11-25 W 700mA	220-240	164	38	24,5	Dimmable DALI	DV1031
Vector 55	11-25 W 600mA	220-240	164	38	24,5	Dimmable DALI	DV1031

\* 1 Driver for Max 3 Spots

# Vector magnetic



Vector magnetic 48Vdc

White  
01  
Fast delivery

Black  
04

Brushed Silver  
15  
Delivery time on demand

Brushed Copper  
18

Brushed Bronze  
20

S


F

WF

IP20


MacAdam 3SDCM

Life L70 (6k) 50000h




Vector 40 magnetic

Dimmable DALI				
W	CRI	Beam	Flux	CCT
10 W	90	S 13°	540 lm	2700K
				3000K
				4000K
		F 20°	584 lm	2700K
				3000K
				4000K
		WF 28°	528 lm	2700K
				3000K
				4000K




Vector 55 magnetic

Dimmable DALI				
W	CRI	Beam	Flux	CCT
26 W	90	S 16°	1492 lm	2700K
				3000K
				4000K
		F 22°	1465 lm	2700K
				3000K
				4000K
		WF 32°	1596 lm	2700K
				3000K
				4000K




Vector 55 zoom magnetic

Dimmable DALI				
W	CRI	Beam	Flux	CCT
23 W	90	F 22°-WF 32°	660 - 1137 lm	2700K
				3000K
				4000K




Vector 40 pendant magnetic

Dimmable DALI				
W	CRI	Beam	Flux	CCT
10 W	90	S 13°	540 lm	2700K
				3000K
				4000K
		F 20°	584 lm	2700K
				3000K
				4000K
		WF 28°	528 lm	2700K
				3000K
				4000K



Vector 55 pendant magnetic

Dimmable DALI				
W	CRI	Beam	Flux	CCT
26 W	90	S 16°	1492 lm	2700K
				3000K
				4000K
		F 22°	1465 lm	2700K
				3000K
				4000K
		WF 32°	1596 lm	2700K
				3000K
				4000K



Accessoires		Vector 40	Vector 55
Color		Code	Code
	Accessories holder	AP90100	AP91100
	Lens for elliptical emission	AP90200	AP91200
	Soft filter	AP90300	AP91300
	Anti-dazzle louvre	AP90400	AP91400
	Adjustable dowsers		AP91500

## Vector is compatible with **Artemide App**

Artemide App is a user-friendly and intuitive interface used to control individual products, groups of appliances and lighting scenarios. It is a tool that can be associated with several products from both Design and Architectural Catalogues.



Download Artemide App  
and find more information on  
[artemide.com](http://artemide.com)

Headquarters

**Artemide S.p.A.**  
Via Bergamo, 18  
20010 Pregnana Milanese (MI), Italy  
Tel. +39 02 93518.1  
Tel. +39 02 93526.1  
Numero verde 800 834 093  
(from Italy only)  
info@artemide.com  
artemide.com

Communication and Marketing  
Department

Via Canova, 34  
20145 Milan (MI), Italy  
Tel. +39 02 349611  
communication@artemide.com  
artemide.com

For information regarding distributors and  
points of sale, please visit artemide.com  
or email: info@artemide.com

**Artemide S.p.A.**  
si riserva la facoltà di modificare, in qualunque  
momento e senza preavviso, le caratteristiche  
tecniche degli elementi illustrati nel presente  
catalogo.

**Artemide S.p.A.**  
reserves the right to change, at any time and  
without prior warning, the technical specifications  
of any product illustrated in this catalogue.

**Artemide S.p.A.**  
se réserve le droit de modifier, à n'importe  
quel moment et sans préavis, les caractéristiques  
techniques des éléments illustrés dans ce  
catalogue.

**Artemide S.p.A.**  
behält sich das Recht vor jederzeit und ohne  
Ankündigung die technischen Daten der im  
Katalog abgebildeten Produkte zu ändern.

**Artemide S.p.A.**  
se reserva la facultad de modificar, en cualquier  
y sin aviso previo, las características técnicas  
de los elementos ilustrados en el presente  
catálogo.





